CO₂ FIRE EXTINGUISHER 5 KG

Model: CS 5- FE

89B				
	B			

	Model	CS 5- FE		
	CAPACITY	5 kg		
	height (mm)	765 mm		
A	Diameter (mm)	140 mm		
AT	Cylinder Material	Steel alloy		
TECHNICAL DATA	EXT AGENT	Carbon Dioxide		
ICA	Test Pressure (bar)	Above 200 bar		
HN	Working Pressure	60 bar		
EC	Weight Full (kg)	13.6 kg		
T	JET Range (m)	6 M		
	Discharge Time(S)	15 SEC		
	Fire Rating	89B		
	Temperature range	-30°C TO +60°C		




METHOD OF USE

Discharge entire contents onto the fire from 1 to 3 metre distance. This extinguisher should be serviced at least once a year by an approved service engineer only in accordance with EN. Recharging should be carried out to EN only using recommended by the manufacturer.

- Fire Extinguisher

NO	DESCRIPTION	NO	DESCRIPTION
1	COMPLETE VALVE	8	DISCHARGE HOSE
2	SAFETY VALVE	9	HORN
3	PISTON	10	AGENT (CO ₂)
4	SAFETY PIN	11	WALL BRACKET
5	SPRING	12	STEEL CYLINDER
6	PLASTIC SEAL	13	LABEL
7	SIPHON TUBE		



SILVA-S.R.L

This data specification sheet provides guidance only. It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, SILVA S.R.L does not accept any responsibility or legal liability for any errors or omissions.